

## 5. Informacje instalacyjne

### 5.1 Legenda

Oprawy:

Kod	Ilość	Oprawa	Źródło światła	Strumień (lm)
A	24	MVP506 A/59	1 * HPI-TP250W SGR	1 * 25000

Sekcje:

Kod	Sekcjonowanie
1	Boisko do piłki nożnej
2	Boisko wielofunkcyjne

### 5.2 Orientacja i rozmieszczenie opraw

Ilość i kod	Pozycja			Kąty nacelowania			Sekcje	
	X (m)	Y (m)	Z (m)	Rot.	Rot90	Rot0	1	2
1 * A	1.00	-0.50	9.00	57.3	67.0	0.0	+	-
1 * A	1.00	33.70	9.00	-57.3	67.0	0.0	+	-
1 * A	1.50	-0.50	9.00	46.5	69.7	0.0	+	-
1 * A	1.50	33.70	9.00	-46.5	69.7	0.0	+	-
1 * A	2.00	-0.50	9.00	30.9	73.9	0.0	+	-
1 * A	2.00	33.70	9.00	-30.9	73.9	0.0	+	-
1 * A	31.25	-0.50	9.00	127.8	63.4	0.0	+	-
1 * A	31.25	33.70	9.00	-127.8	63.4	0.0	+	-
1 * A	31.75	-0.50	9.00	52.2	63.4	0.0	+	-
1 * A	31.75	33.70	9.00	-52.2	63.4	0.0	+	-
1 * A	61.10	-0.50	9.00	149.1	73.9	0.0	+	-
1 * A	61.10	33.70	9.00	-149.1	73.9	0.0	+	-
1 * A	61.60	-0.50	9.00	133.5	69.7	0.0	+	-
1 * A	61.60	33.70	9.00	-133.5	69.7	0.0	+	-
1 * A	62.10	-0.50	9.00	122.7	67.0	0.0	+	-
1 * A	62.10	33.70	9.00	-122.7	67.0	0.0	+	-
1 * A	64.00	-0.50	9.00	65.1	62.7	0.0	-	+
1 * A	64.00	33.70	9.00	-65.1	62.7	0.0	-	+
1 * A	64.50	-0.50	9.00	55.0	62.1	0.0	-	+
1 * A	64.50	33.70	9.00	-55.0	62.1	0.0	-	+
1 * A	82.50	-0.50	9.00	125.0	62.1	0.0	-	+
1 * A	82.50	33.70	9.00	-125.0	62.1	0.0	-	+
1 * A	83.00	-0.50	9.00	114.9	62.7	0.0	-	+
1 * A	83.00	33.70	9.00	-114.9	62.7	0.0	-	+